

B3 / Tam parametre sicili

R02 / Birim mm / 2026-10-04

PARAMETRE / DEĞER / SINIF

Code: TI-TS-B14A

FaceSide: 600

LowerEdge: 2200

SheetThickness: 2

RailLength: 400

RailHeight: 35

RailDepth: 20

RailWall: 2

RailZ: [2350, 2650]

StudX: [-150, 150]

StudDiameter: 8

StudLength: 30

SlotWidth: 9

SlotLength: 18

PostDiameter: 60.3

PARAMETRE / DEĞER / SINIF

PostWall: 3.2

PostBottom: -600

PostTop: 2800

PostY: -60

ClampID: 61

ClampWall: 3

ClampWidth: 40

EarHole: 9

EarCenters: 90

ClampBoltDiameter: 8

ClampBoltLength: 50

FoundationSide: 400

FoundationBottom: -700

Colour: approved B14a face / galvanized back



+90 532 711 2185
info@trafficindustries.com
trafficindustries.com
mirgrp.com

Macun Mah. Batı Bulvarı
ATB İş Merkezi No.192
06105 Yenimahalle · Ankara · Türkiye

TI-TS-B14A

BELGE TI-TS-B14A	REV R02	ÖLÇEK Görünüşte	SAYFA 3/3
TARİH 2026-10-04	BİRİM mm	KAĞIT A3 / 420x297	DİL TR