

LANE GUIDANCE & DELINEATION · SPECIFICATION TEXT

TPU flexible delineator post

1. Subject and scope

This specification covers the supply of tpu flexible delineator post. The function and place of use follow the definition below:

The flexible delineator post is designed to separate lines where a permanent obstacle is unwanted but crossing is unwanted too. The TPU body lays over under impact and spends the blow by flexing; the flexible delineator post rights itself and leaves the striking vehicle undamaged. It is flexible, durable and removable. Its socket base lets the route be opened by hand. The flexible delineator post is used on island noses, in lane separation, at car park entrances, on service roads and along cycle lanes.

2. Features

Rights itself after impact; the TPU body keeps its shape through repeated flexing.

The socket type lifts out of the ground, so the same post serves one temporary closure after another.

The number and position of reflective collars are chosen from the sight distance on the route.

Base diameters from 120 mm to 260 mm; the wider base resists toppling on windy or heavily trafficked sites.

3. Dimensions and classes

Height	300 · 450 · 750 · 1000 mm (market-standard heights; other heights by quotation)
Base diameter	Ø 120 · 180 · 200 · 260 mm
Material	TPU · TPE
Weight	0.49–2.1 kg
Mounting	Socket (removable) or dowelled fixed base

Note: values are production-programme and market-standard ranges; order dimensions are fixed in the quotation.

4. Documentation

The governing document and standard are stated in writing at quotation.

Test results and documents are shared only with the report and the document; no class name is cited without its document.

5. Packing and delivery

Posts ship without bases, and the bases travel in separate cartons · Pallet size and gross weight are stated on the packing list · Mixed-height loads are accepted · The container count follows the height chosen and is quoted with the pallet number

6. Quotation and contact

Quotation requests go through trafficindustries.com or info@trafficindustries.com; the quotation is prepared the same day against quantity, variant and delivery terms.