

Wheel stops

The wheel stop goes down at the end of the bay to settle where the vehicle halts without arguing with the driver. The rubber body takes the blow by compressing and holds its shape; the wheel stop halts the tyre before the bumper reaches the wall. It is durable, reflective-striped and dowel-fixed. The yellow reflective strip marks the spot on a dim level. The wheel stop is used in covered and open car parks, at charging points and in front of loading doors.

FEATURES

- The rubber body stops the vehicle without damaging the tyre or wheel trim.
- Yellow reflective strips keep it visible in a covered car park and outdoors at night.
- Countersunk fixing holes sit below the surface, so no bolt head touches a tyre.
- Modular — sections butt together to suit a longer bay.

TECHNICAL SUMMARY

Body / size	8.5 · 10 · 50 · 55 · 110 · 180 cm
Rubber market classes	1650 · 1830 · 1860 × 150 × 100 mm · wheel type 600×120×100 mm
Material	NR/SBR rubber · Polypropylene · PVC
Weight	1.9–19 kg (by type and length)
Mounting	Ø10×110 mm coach screw + plug
Model identity	A wheel stop model is defined by the three axes length × width × height, the material, the mass, the hole count/pattern and the delivery kit; a length list alone does not identify a model

Values are production-programme and market-standard ranges; final dimensions are given in writing with the quotation.

WHERE IT IS USED

- Covered car park. The wheel stop prevents contact with columns and walls; the reflective strip marks it on a dim level.
- Open car park. The wheel stop fixes the parking layout more permanently than a painted line.
- Charging point. The wheel stop halts the vehicle within reach of the cable.
- Plant and warehouse floor. The wheel stop sets the approach limit in front of a loading door.

STANDARDS AND DOCUMENT LANGUAGE

Manufactured to the order specification in the Turkish market. The Australian market speaks of wheel stops through the parking design standard AS/NZS 2890.1; conformity is written with the supplier document. Test results and certificates are shared with the report and the document.